

## Features:

- Slimline Constant Voltage Driver
- Flicker Free
- AC input: 200-240VAC
- Built in PFC Function
- Efficiency up to 85%
- Protections: short circuit/ over loading/ over current/ over temperature
- Full protection plastic housing easy installation
- Cooling by free air convection
- Suitable for profile lighting and lightboxes



## Models

### ECP45-12VF-1

### ECP45-24VF-1

## Output Specifications

	ECP45-12VF-1	ECP45-24VF-1
Output Voltage	12V	24V
Voltage Tolerance	180mV	
Output Current	3.75A	1.875A
Rated Power	45W	

## Input Specifications

Input Voltage	200-240VAC
Frequency Range	50-60Hz
Inrush Current	<60A
Full Load Efficiency (Typ.)	85%
AC Current (Max.)	0.3A
Power Factor	PF >0.9/240VAC (Full Loading)

## Protection

Short Circuit	Shut down o/p voltage, re-power onto recover after fault condition is removed
Over Loading	<120%, Shut down o/p voltage, re-power onto recover
Over Temperature	115°C shut down o/p voltage, re-power on to recover
Protection Class	II

## Environment

Working Temperature	-20~+45°C (Refer to derating curve), +85°C (max case temp.)
Working Humidity	45-85%

## Safety & EMC

Safety standards	EN613471, EN61347-2-13
------------------	------------------------

## Safety & EMC

EMS	EN6 1000-3-2; EN61000-3-3; EN61547
EMF	EN62493-2010
ERP	EN1194-2012

## Other Specifications

IP Rating	IP20
Weight	0.16 Kg
Size	251 x 30 x 16 mm
Packing	400 x 268 x 235 mm (100PCS/CTN)

## Mechanical Specifications

